



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ7H7 ZCKJD37H7 ZCKJD31 ZCKJ11 ZCKJ21H29 ZCKJ6H29 ZCKJD39H29 ZCKJ21 ZCKJ5 ZCKJD39 ZCKJ8H29 ZCKJD31H7 ZCKJ2H7 ZCKJ9H29 ZCKJ6 ZCKJ5H7 ZCKJ7 ZCKJD37H29 ZCKJ2 ZCKJ41 ZCKJ1 ZCKJ11H29 ZCKJ7H29 ZCKJD35H7 ZCKJ6H7 ZCKJ8 ZCKJD35 ZCKJ1H29 ZCKJ5H29 ZCKJ9H7 ZCKJ4H7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ11H7  
 ZCKJ4H29  
 ZCKJD35H29  
 ZCKJ41H29  
 ZCKJD31H29  
 ZCKJD39H7  
 ZCKJD37  
 ZCKJ8H7  
 ZCKJ41H7  
 ZCKJ21H7  
 ZCKJ4  
 ZCKJ1H7  
 ZCKJ2H29  
 ZCKJ9

Movement of operating head	Linear Rotary
Type of operator	Roller lever plunger spring return metal
Type of approach	Lateral approach, 1 direction

### Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

### Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

### Packing Units

Package 1 Weight	0.195 kg
Package 1 Height	0.450 dm
Package 1 width	0.580 dm
Package 1 Length	0.630 dm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------