

## bells for industrial and alarm use



0 414 62

0 413 49

0 414 19

Pack	Cat.Nos	<b>Class I</b>			
		Double insulated Polyester corrosion resistant finish 200 hours maxi. continuous rating			
		<b>IP 44 - IK 10 - Direct current version</b> Ø150 mm gong			
1	RAL 3000 Red 0 414 62	Voltage = 24 V	Average Consumption (mA) 70	Average acoustic output at 1 m (dB) 90	Weight (kg) 1
		<b>IP 40 - IK 08 - 50/60 Hz - Alternating current version</b> Ø100 mm gong			
1	RAL 7037 Grey 0 413 49	Voltage ~ 230 V	Consumption (mA) 50	Average acoustic output at 1 m (dB) 95	Weight (kg) 0.8
		<b>IP 44 - IK 10</b> Ø150 mm gong			
1	0 414 16	24V	360	98	1
1	0 414 18	110/130 V	90	98	1
1	0 414 19	230 V	50	98	1
		<b>IP 44 - IK 10</b> Ø250 mm gong			
1	0 414 39	230 V	70	98	2.1

## electromechanical sirens



0 415 23

0 415 33 with claws

Technical characteristics p. 371

Pack	Cat.Nos	<b>Industrial warning devices 110 dB</b> <b>IP 20 - IK 08</b>		
		Frequency 350/400 Hz, continuous sound Operates intermittently: 1 min on / 10 min off		
1	0 415 20	24 V~ and = power supply 230 V~ power supply	Consumption in mA	
1	0 415 23		820	120

		<b>Electromechanical sirens IP 30 - IK 05</b>					
		Supplied with screws for semi-flush mounting					
		<b>D.C. current</b>					
		Voltage =	Power (W)	Consumption (mA)	Average acoustic output at 1 m (dB)	Weight (kg)	Max. continuous rating (hr)
1	0 415 32	12 V	11	889	98	0.2	200
1	0 415 33	24 V	12	516	100	0.2	200
		<b>A.C. current - 50/60 Hz</b>					
		Voltage ~	Power (W)	Consumption (mA)	Average acoustic output at 1 m (dB)	Weight (kg)	Max. continuous rating (hr)
1	0 415 36	24 V	12.5	531	100	0.2	200
1	0 415 38	110 V	70	400	105	0.35	100
1	0 415 39	230 V	57	250	105	0.35	100

		<b>Multi-sound electronic sirens</b>	
		97 to 106 dB 16 electronic sounds possible for identification of each defined event Easy to identify and select sounds for each appliance using coded wheel Adjustable sound level	
1	0 415 45	230 V~, IP 44 - IK 07	