SIEMENS

Data sheet

6GK1901-1BB10-2AA0

Product type designation

Product description

IE FC RJ45 Plug 180 (2x2)

RJ45 data connector

Industrial Ethernet FastConnect RJ45 plug 180 2x 2, RJ45 plug-in connector (10/100 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC Cable 2x 2; 180° cable outlet 1 pack = 1 unit



Suitability for use For connection to IE FC TP cables 2x2, suitable for fast assembly with the FastConnect system

| Transmission rate | |
|---|-----------------------|
| Transfer rate / for Industrial Ethernet | 10 Mbit/s, 100 Mbit/s |

| Interfaces | |
|--|---|
| Number of electrical connections | |
| for Industrial Ethernet FC TP cables | 4 |
| for network components or terminal equipment | 1 |
| Type of electrical connection | |
| • for Industrial Ethernet FC TP cables | integrated cut-and-clamp contacts for 4-wire TP FC installation cable |
| • for network components or terminal equipment | RJ45 connector |
| Type of electrical connection / FastConnect | Yes |

| Mechanical data | |
|-----------------------------|-------|
| Material / of the enclosure | metal |
| Number of reuses | 10 |
| Locking mechanism design | other |

| Design, dimensions and weight | |
|---------------------------------|-------------------|
| Type of cable outlet | 180° cable outlet |
| Width | 13.7 mm |
| Height | 16 mm |
| Depth | 55 mm |
| Net weight | 35 g |
| Connectable cable cross-section | 6.5 6.5 mm |

| Permitted ambient conditions | |
|--|------------|
| Ambient temperature | |
| during operation | -40 +85 °C |
| during storage | -40 +85 °C |
| during transport | -40 +85 °C |
| Relative humidity / at 25 °C / without condensation / during operation / maximum | 95 % |
| Protection class IP | IP20 |

| Product properties, functions, components / general | |
|---|-----|
| Product feature | |
| PoE capability | Yes |
| PoE+capability | Yes |
| • silicon-free | Yes |
| Product component | |
| • strain relief | Yes |

| Standards, specifications, approvals | |
|---|------|
| Certificate of suitability | |
| RoHS conformity | Yes |
| UL approval | Yes |
| • cULus approval | Yes |
| Railway application in accordance with EN 50155 | No |
| Standard for structured cabling | Cat5 |

Further Information / Internet Links Internet-Link

| ternet-Link | |
|---|--|
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAx Download Manager | http://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |
| | |

10/30/2018 🖸 last modified: