

USB PC cable for connection to the USB interface of a PC, for communication with SIMOCODE pro or SIRIUS 3RW44 soft starter or modular safety system 3RK3 via the system interface



| General technical data:  |                |
|--------------------------|----------------|
| Product brand name       | SIRIUS         |
| Product designation      | USB PC cable   |
| Ambient temperature      |                |
| • during storage         | -40 ... +80 °C |
| • during operation       | -25 ... +60 °C |
| • during transport       | -40 ... +80 °C |
| Certificates/ approvals: |                |

| General Product Approval | EMC | Test Certificates |  | Shipping Approval |
|--------------------------|-----|-------------------|--|-------------------|
|--------------------------|-----|-------------------|--|-------------------|



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



| Shipping Approval | other |  |  |  |
|-------------------|-------|--|--|--|
|-------------------|-------|--|--|--|



GL



RMRS

[Confirmation](#)

[PROFINET-Certification](#)

[PROFIsafe-Certification](#)



Profibus

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7941-0AA00-0>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7941-0AA00-0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3UF7941-0AA00-0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3UF7941-0AA00-0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7941-0AA00-0&lang=en)



