

# Plug PowerTOP Xtra

Part Number: 13620



## MENNEKES

Elektrotechnik GmbH & Co. KG  
Aloys-Mennekes-Straße 1  
57399 KIRCHHUNDEM GERMANY  
[www.MENNEKES.org](http://www.MENNEKES.org)

# Product Description

- screw connection technology ErgoCONTACT
- ergonomic enclosure design with nubbed grip zones
- rubberised cable gland with sealing
- rubberised bayonet ring
- sealed against dust, temporary submersion and high pressure cleaning
- strain relief and protection against kinking
- thread lock and safety slide
- area for self-adhesive labels

# Technical Details

| Plug - PowerTOP Xtra         | 13620                                    |
|------------------------------|------------------------------------------|
| Product series               | PowerTOP Xtra                            |
| Ampere                       | 16A                                      |
| UL-Ampere                    | 13620                                    |
| Number of Poles              | 3p                                       |
| Clock position               | 6h                                       |
| Voltage                      | 230V                                     |
| Hertz                        | 50-60 Hz                                 |
| Current Type                 | AC                                       |
| Protection Type              | IP67/IP69                                |
| Contact carrier              | Standard                                 |
| Pilot contact                | Without pilot contact                    |
| Connection                   | Screw terminals - ErgoCONTACT            |
| Screw drive contact screw    | Combination head screw (PZ2 and slotted) |
| Phase inverter plugs         | Without phase inverter                   |
| Conductor cross-section min. | 1 mm <sup>2</sup>                        |

|                              |                            |
|------------------------------|----------------------------|
| Conductor cross-section max. | 2,5 mm <sup>2</sup>        |
| Cable kink protection        | Integrated in cable gland  |
| Protective grommet           | Without protective grommet |
| Protective cap               | Without protective cap     |
| EAN / Identification number  | 4015394302421              |

### Permissible ambient conditions

|                                           |                 |
|-------------------------------------------|-----------------|
| Permanent ambient temperature min. - max. | -25 °C - +40 °C |
|-------------------------------------------|-----------------|

### Material properties

|            |                                       |
|------------|---------------------------------------|
| Cover      | PA6<br>similar RAL 7000 squirrel grey |
| Front part | PA6<br>similar RAL 5007 blue          |


### Material resistance

The material resistance overview can be found on the website in the section "Knowledge" → "Product knowledge" → "Materials"

## Regulations and Standards

|                                   |             |
|-----------------------------------|-------------|
| RoHS 2011/65/EU incl. 2015/863/EU | ✓           |
| POP Regulation (EU) 2019/1021     | ✓           |
| Norm(s)                           | IEC 60309-2 |
| Declaration of conformity         | CE          |
| Certification                     | -           |

# Dimensional drawing



| Zeichnung               | Amp.       | 16   |       |       | 32   |      |      |
|-------------------------|------------|------|-------|-------|------|------|------|
|                         |            | 3    | 4     | 5     | 3    | 4    | 5    |
| 2 MB 256                | Pole       |      |       |       |      |      |      |
|                         | Maße in mm |      |       |       |      |      |      |
|                         | a          | 154  | 163   | 163   | 196  | 196  | 196  |
|                         | b          | 73   | 81    | 89    | 95   | 95   | 102  |
|                         | n          | 121  | 129   | 129   | 154  | 154  | 154  |
| y von                   |            | 7    | 8     | 8     | 10,5 | 10,5 | 13,5 |
| bis max. mm             |            | −13  | −15,5 | −15,5 | −18  | −18  | −20  |
| Klemmen für Leiterquer- |            | 1    | 1     | 1     | 2,5  | 2,5  | 2,5  |
| schnitt von bis mm²     |            | −2,5 | −2,5  | −2,5  | −6   | −6   | −6   |