

Quartz time switch Day 1 change-over contact 230V/50-60Hz 3 MW



Figure similar

Model	
Product brand name	SENTRON
Product designation	Timers
Design of the product	Days
Design of the switching function	CO contact
General technical data	
Manner of function	
• line-synchronous	No
• quartz-controlled	Yes
Accuracy / per day	2.5 s
Shortest switching time interval / of channel 1	30 min
Supply voltage	
Supply voltage / initial value	230 V
Supply voltage / Full-scale value	230 V
Supply voltage frequency	
• minimum	50 Hz

• maximum	50 Hz
Type of voltage / of the supply voltage	AC

Protection class	
Protection class IP	IP20

Switching capacity	
Switching capacity current / at AC / at 250 V / Rated value	16 A

Product details	
Product feature / floating switching contact	Yes

Product function	
Product function	
• 60 min time program	No
• Automatic daylight-saving adjustment	No
• direct operation	Yes
• annual time program	No
• Switching preselection	Yes
• 24-hour time program	Yes
• Weekly time program	No

Number	
Number of channels	1

Mechanical Design	
Height	83 mm
Width	53 mm
Depth	64 mm
Number of width units	3
Mounting type	DIN rail
Net weight	157 g

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=7LF5301-6>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7LF5301-6>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7LF5301-6

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

