

CAT. N° 0 280 89



AIR CIRCUIT BREAKER DMX³ 1600 DRAW-OUT VERSION - BREAKING CAPACITY 50KA - 4P - 1250A

| | |
|---------------------------|-----|
| Pack (number of units) | O/R |
| Volume (dm ³) | O/R |
| Weight (g) | O/R |

Product characteristics

Draw-out version

- Supplied with :
 - 4 auxiliary contacts: NO/NC
 - door sealing
- To be installed on a draw-out base Cat.No 0 281 53 or 0 281 54

Breaking capacity Icu 50 kA (415 V~)

- Frame 1600
- 4P
- In : 1250 A

General characteristics

Air circuit breakers DMX³ 1600 - from 630 to 1600 A

- Automatic air circuit breakers must be equipped with DMX³ 1600 electronic protection units Cat.No 0 281 64/65/66, imperatively ordered together for factory assembly
- Please ask for DMX³ order form
- Conform to IEC 60947-2

Documentation

Catalogue pages & additional information

- [Description page \(p.156\)](#)

Installation & technical data

- [F02194EN_04_DMx3_1600v0](#)
- [EXB20072_logic_selectivity \(print\)](#)
- [LE10707AA](#)

Installation instructions & related documents

- [LE08437AC](#)