Product data sheet Characteristics

LV429492

Earth-leakage VigiPacT add-on protection module, ComPacT NSX 250, 200 VAC to 440 VAC, 30 mA to 30 A, 3 poles





Main

ComPacT NSX100250 new generation
ComPacT new generation
VigiPact
Vigi add-on
Wiring
ComPacT NSX250 new generation circuit breaker
3P
250 A
Class A Class AC
Adjustable
0.03 A for class A 0.1 A for class A 0.3 A for class A 0.5 A for class A 1 A for class A 3 A for class A 10 A for class A 30 A for class A
Adjustable
0 ms 60 ms 150 ms 300 ms 500 ms 800 ms 1.2 s

Complementary

50/60 Hz
03/00 1.2
200440 V AC 50/60 Hz conforming to IEC 60947-2
With
800 ms
IV

Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	1.5 kg	
Package 1 Height	1 dm	
Package 1 width	1.1 dm	
Package 1 Length	0.9 dm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
PVC free	Yes	