

CAT. N° 4 122 82



SPD - HIGH RISK LEVEL INSTALLATION - T1+T2 - LIMP 25 KA/POLE - 3P

Pack (number of units)	1
Volume (dm ³)	2,363
Weight (g)	1 227,00

Product characteristics

SPDs for high risk level installations

- SPDs for big installations with external lightning protection (LPS) and for high risk level installations according to EN/IEC 62305 standards
- SPDs with plug-in modules and status indicators:
 - Green: SPD operational
 - Red: plug-in modules to be replaced

T1 + T2 - limp 25 kA/pole

- Up: 1.5 kV - Uc: 350 V~
- Earthing systems: TT, TNC, TNS.
- Recommended MCCB: DPX³ 160 - 80 A
- Number of poles : 3P
- Itotal (10/350) : 75 kA
- Remote status monitoring (FS contact) : Yes
- Number of modules : 6

General characteristics

Class I + II (T1+T2) low voltage SPDs

- Protection against transient overvoltages for 230/400 V~ power networks (50/60 Hz).
- SPDs compliant with EN/IEC 61643-11 standards
- Recommended for main distribution boards
- Class I+II (T1+T2) : SPDs tested and specified according to both T1 and T2 test classes

Documentation



Catalogue pages & additional information

- [Technical page \(p.074-075\)](#)
- [Description page \(p.076\)](#)
- [Technical page \(p.079\)](#)
- [Technical page \(p.080-081\)](#)
- [Dimensions of din-rail equipment](#)



Installation & technical data

- [F02063EN-03](#)



Installation instructions & related documents

- [LE07114AA-04](#)



Agreements & certificates of conformity

- [OC / CB-NL-49804](#)