



# Essential SmartBright G5 LED Floodlight

BVP150 LED200/CW PSU 200W SWB G3 GM

Essential SmartBright G5 LED Floodlight, 20000 lm, 200 W, 865 cool daylight, 110°, Safety class I, Mounting bracket

The Essential SmartBright G5 LED Floodlight is the new successor with robust die-cast aluminum housing suitable for general outdoor application. Lightweight, with a robust die-cast aluminum housing and corrosion-proof coating, it's suitable for general outdoor applications. Plus, with a higher efficacy than the previous generation, it also saves more energy.

## Product data


General Information	
Number of gear units	1 unit
Gear	-
Driver included	Yes
Light source engine type	LED
Warranty period	2 years
Light Technical	
Luminous Flux	20,000 lm
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	100 lm/W
Color rendering index (CRI)	80
Number of light sources	1
Beam angle of light source	110 degree(s)
Light source color	865 cool daylight
Optic type	Wide beam

Luminaire light beam spread	110°
Effective projected area	0.12 m²
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Inrush current	10 A
Inrush time	0.03 ms
Power Consumption	200 W
Power Factor (Fraction)	0.9
Connection	Flying leads/wires
Cable	Cable 0.7 m without plug
Number of products on MCB of 16 A type B 11	
Suitable for random switching	No
Protection class IEC	Safety class I

# Essential SmartBright G5 LED Floodlight

Controls and Dimming	
Dimmable	No
Control interface	-
Maximum dim level	Not applicable
Mechanical and Housing	
Housing Material	Aluminum die-cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover material	Glass
Housing Color	Black
Mounting device	Mounting bracket
Optical cover finish	Clear
Overall length	457 mm
Overall width	335 mm
Overall height	39 mm
Dimensions (Height x Width x Depth)	39 x 335 x 457 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Optical cover type	Tempered glass
Net Weight (Piece)	2.900 kg
Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	No

## Dimensional drawing



ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Ambient temperature range	-40 to +50 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.31, 0.34) SDCM≤6
Power consumption tolerance	+/-10%
Product Data	
Order product name	BVP150 LED200/CW PSU 200W SWB G3 GM
Full product name	BVP150 LED200/CW PSU 200W SWB G3 GM
Full product code	872016952231299
Order code	911401838286
Material Nr. (12NC)	911401838286
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169522312
Numerator - Packs per outer box	6
EAN/UPC - Case	8720169522558

## Essential SmartBright G5 LED Floodlight

