



Downlight

Mayores beneficios,
al menor costo.



Especificaciones

80

CRI



100-240 V



15,000 h



No dimerizable

Nombre comercial	PILA DL052 R Rd LED 1300 65K 18W 8" WV	PILA DL052 R Rd LED 2000 65K 24W 11" WV	PILA DL052 SF RD LED 1300 65K 18W 8" WV	PILA DL052 SF RD LED 2000 65K 24W 11" WV
12NC	929004076502	929004076802	929004078902	929004079202
Potencia (W)	18	24	18	24
Flujo luminoso (lm)	1.300	2.000	1.300	2.000
Eficiencia (lm/W)	72	83	72	83
Temperatura de color (K)	6.500	6.500	6.500	6.500
Factor de potencia	> 0.5	> 0.5	> 0.5	> 0.5
IP	IP20	IP20	IP20	IP20
Formato	Circular, embutido	Circular, embutido	Circular, sobrepuesto	Circular, sobrepuesto
Reemplazo (W)	-	-	-	-

Beneficios:

- ▶ Confiabilidad
- ▶ Ahorro de energía
- ▶ Amplio rango de aplicación
- ▶ 1 año de garantía

Aplicaciones:

- ▶ Residencial
- ▶ Escuelas
- ▶ Hotelería
- ▶ Oficinas

Datos comerciales

Nombre comercial	Diámetro de corte (mm)	Diámetro exterior (mm)	EAN	Cant x caja
PILA DL052 R Rd LED 1300 65K 18W 8" WV	203	220	8727900973358	12
PILA DL052 R Rd LED 2000 65K 24W 11" WV	280	295	8727900973419	12
PILA DL052 SF RD LED 1300 65K 18W 8" WV	N/A	210	8727900973778	12
PILA DL052 SF RD LED 2000 65K 24W 11" WV	N/A	280	8727900973839	12