

CAT. N° 3 372 26



XL³ S 160 FLUSH-MOUNTING 24-MODULES PER ROW CABINET WITH FIXING LUGS - RAL 9003 - 6 ROWS - 144 MODULES - 1112X667X138 MM

Pack (number of units)	1
Volume (dm ³)	109,775
Weight (g)	23 444,00

Product characteristics

Flush-mounting 24-module per row cabinets

- Supplied with fixing lugs
- Faceplates: RAL 9003
- Number of rows : 6
- Number of modules : 144
- Height : 1112 mm
- Width : 667 mm
- Depth : 138 mm

General characteristics

XL³ S 160 - 24 modules per row - "ready to use" metal distribution cabinets

- Cabinets supplied with rails fitted (150 mm fixing centres) and full height faceplates
- Doors and terminal blocks to be ordered separately
- Take DPX³ 160 and modular protection devices
- Used to create assemblies certified IEC 61439-2 and -3
- IP 40 with door
- IP 30 without door
- Cut-outs in top and bottom for feeding cables through
- Can take Lina 25 ducting

Documentation

Catalogue pages & additional information

- [Description page \(p.226\)](#)
- [Technical page \(p.229\)](#)

Installation & technical data

- [F02368EN-02](#)
- [EXB17042_CA_XL3S160_EN](#)

Environmental product profile

- [LGRP-00470-V01](#)

Installation instructions & related documents

- [LE10065AF](#)

Agreements & certificates of conformity

- [LOVAG-IT 18](#)
- [LOVAG-IT 17](#)
- [LOVAG-IT 17](#)
- [LOVAG-IT 18](#)