


Product sheet



XL³ LEGRAND

Modular distribution board with staggered bars, 4-pole 160 A - external output - 15 connections/bar - 10 modules

REF. 400411 | EAN. 3414971978713

[> Visit e-catalogue](#)

Product characteristics

- External Inputer 35 - 70 mm² solid or 35 - 70 mm² stranded with or without ferrule
- 14 Output : 2 x 10 - 35 + 4 x 10 - 25 + 8 x 2.5 - 10 mm² rigid conductor
- 14 output : 1 x 10 - 25 + 1 x 10 - 16 + 4 x 6 - 16 + 8 x 1.5 - 10 mm² flexible conductor with or without ferrule
- In = 160A - 40°C Ui = 500 V
- Ipk = 27 kA - 60 ms Icw = 8,4 kA - 1s

The product's benefits

Installation

- Easy and fast cabling and connecting thanks to a maximised cabling space , optimized "orientation" of bars and adapted dimensions and positions of connections

Usage

- Easy connection thanks to appropriate connection sizing

Avantages

- High capacity external input to simplify wiring
- Optimised bar orientation for easy cable access
- Connections sized to facilitate connection and answer all needs

Documentation

TECHNICAL DOCUMENTATION

F03358EN-02.pdf | PDF (2.35Mo)

F03358FR-02.pdf | PDF (1.79Mo)

CATALOGUE PAGE & OTHERS

ex223001_0299.pdf | PDF (0.13Mo)