

# horizontal and vertical cabling

configure your LCS<sup>2</sup> system (continued)

## VERTICAL POWER DISTRIBUTION UNITS (PDU) (p. 95)

	PDU 2P+E	24 x 2P+E sockets	French standard	0 465 80
			German standard	0 465 88
			British standard	0 465 89
		24 x C13 sockets		0 465 81
		24 x C13 + 6 x C19 sockets Cord with IEC 60309 plug		0 465 84
		24 x C13 + 3 x C19 sockets Cord with IEC 60309 plug 3-phase supply		0 465 85

## SELECT FIBRE OPTIC PATCH CORDS (p. 83)

			OS1/OS2 (UPC) monomode 9/125 µm	OM 3 multimode 50/125 µm	OM 2 multimode 50/125 µm
	SC/SC duplex cords	1 m	0 326 00	0 326 09	0 330 69
		2 m	0 326 01	0 326 10	0 330 70
		3 m	0 326 02	0 326 11	0 330 71
	SC/LC duplex cords	1 m	0 326 03	0 326 12	0 330 75
		2 m	0 326 04	0 326 13	0 330 63
		3 m	0 326 05	0 326 14	0 330 76
	ST/SC duplex cords	2 m	-	-	0 330 72
		3 m	-	-	0 330 73
	LC/LC duplex cords	1 m	0 326 06	0 326 15	-
		2 m	0 326 07	0 326 16	0 330 61
		3 m	0 326 08	0 326 17	-

## SELECT OPTIC CABLES (2000 m REELS) (p. 77)

	Internal/external, anti-rodent	6 fibres	0 325 12	0 325 10	0 325 08
		12 fibres	0 325 14	0 325 11	0 325 09
	External, anti-rodent reinforced steel	6 fibres	0 325 13	-	-

## SELECT PATCH CORDS AND RJ 45 USER CORDS (p. 63, 67, 72)

	S/FTP	Impedance 100 Ohms	1 m	0 517 80	0 517 52	-
			2 m	0 517 81	0 517 53	-
			3 m	0 517 82	0 517 54	-
			5 m	0 517 83	0 517 55	-
	F/UTP	Impedance 100 Ohms	1 m	-	0 517 62	0 516 40
			2 m	-	0 517 63	0 516 41
			3 m	-	0 517 64	0 516 42
			5 m	-	0 517 65	0 516 43
	U/UTP	Impedance 100 Ohms	1 m	0 518 82	0 517 72	-
			2 m	0 518 83	0 517 73	-
			3 m	0 518 84	0 517 74	-
			5 m	0 518 85	0 517 75	-

## SELECT COPPER CABLES (305 or 500 m REELS) (p. 63, 67, 72)

	S/FTP	4 pairs	500 m	0 327 77	-	-
	SF/UTP	4 pairs	500 m	-	0 327 57	-
		2 x 4 pairs	500 m	-	0 328 59	-
	F/UTP	4 pairs	305 m	-	0 328 56	0 327 52
		4 pairs	500 m	0 327 78	0 327 56	0 328 50
		2 x 4 pairs	500 m	0 328 78	0 327 76	0 327 74
	U/UTP	4 pairs	305 m	-	0 327 54	0 327 50
		4 pairs	500 m	0 327 87	0 328 61	0 328 53
		2 x 4 pairs	500 m	-	0 328 63	-

## SELECT 19" LCS<sup>2</sup> WALL-MOUNTING CABINETS AND EQUIPMENT (p. 92)

			FIXED		PIVOTING
			Depth 400 mm	Depth 580 mm	Depth 600 mm
	6 U	Height 350 mm	0 462 00	-	-
	9 U	Height 500 mm	0 462 01	0 462 06	0 462 11
	12 U	Height 600 mm	0 462 02	0 462 07	0 462 12
	16 U	Height 800 mm	0 462 03	0 462 08	0 462 13
	21 U	Height 1000 mm	-	0 462 09	0 462 14
	Fixed shelves		Depth 115 mm	0 465 00	0 465 00
			Depth 200 mm	0 465 01	0 465 01
			Depth 360 mm	-	0 465 02
	Equipment		Cable entry plate with brush	-	0 462 55
			230 V~ fan	0 462 60	0 462 60
			Thermostat	0 348 48	0 348 48
			Set of 4 casters	-	0 462 64